

Distributed by:

GP Batteries

Product Portfolio

GP Batteries

WORLDWIDE HEADQUARTERS

Hong Kong
GPI International Limited

Gold Peak Building, 8/F., 30 Kwai Wing Road, Kwai Chung, N.T., Hong Kong
Tel : (852) 2484 3333 Fax : (852) 2480 5912
E-mail address : gpil@goldpeak.com Website : http://www.gpbatteries.com.hk

SALES AND MARKETING BRANCH OFFICES

ASEAN

GP BATTERY MARKETING (SINGAPORE) PTE. LIMITED
97 Pioneer Road, Singapore 639579
Tel: (65) 6559 9760 Fax: (65) 6559 9761

MALAYSIA

GP BATTERY MARKETING (MALAYSIA) SDN. BHD.
Lot 8, Jalan Pemberita U1/49,
Temasya Industrial Park,
40150 Shah Alam, Selangor Darul Ehsan, Malaysia
Tel: (60) 3 5569 3499 Fax: (60) 3 5569 3498

THAILAND

GP BATTERY MARKETING (THAILAND) CO., LTD.
102 Soi Sukhumvit 26, Sukhumvit Road,
Klongton, Klongtoey,
Bangkok 10110 Thailand
Tel: (66) 2 661 3688 Fax: (66) 2 661 3602

TAIWAN

GOLD PEAK INDUSTRIES (TAIWAN) LIMITED - TAIPEI OFFICE
Room 1200, International Trade Building, No.205 Sec.1,
Tun Hua South Road, Taipei 10647, Taiwan R.O.C.
Tel: (886) 2 2741 4919 Fax: (886) 2 2731 4868/2741 0912

CHINA

HUIZHOU CHAO BA BATTERY TECHNOLOGY CO., LTD
2/F., South of Hongye Industrial Building,
Tianluo Mountain, 14th Industrial District,
Huizhou City, Guangdong, China
(Postal Code: 516003)
Tel: (86) 752 282 8428 Fax: (86) 752 280 2872

HONG KONG

GP BATTERY MARKETING (H.K.) LIMITED
Gold Peak Building, 8/F., 30 Kwai Wing Road,
Kwai Chung, N.T., Hong Kong
Tel: (852) 2420 0281 Fax: (852) 2494 9349

KOREA

GP BATTERY MARKETING (KOREA) LIMITED
Kunsul Hoekwan Building, 9/F., 71-2 Non Hyun-Dong,
Kang Nam-Gu, Seoul, South Korea
Tel: (82) 2 549 7188/9, 2516 3936/7
Fax: (82) 2 514 0623, 2516 0621

U.S.A.

GOLD PEAK INDUSTRIES (NORTH AMERICA) INC.
11235 West Bernardo Court, San Diego,
CA 92127-1638, U.S.A.
Tel: (1) 858 674 6099 Fax: (1) 858 674 6496

CANADA

GP BATTERY MARKETING INC.
Unit 7, 7780 Woodbine Avenue, Markham,
Ontario, Canada L3R 2N7
Tel: (1) 905 474 9507 Fax: (1) 905 474 9452

LATIN AMERICA

GP BATTERY MARKETING (LATIN AMERICA) INC.
8370 NW, 66th Street, Miami, Florida 33166, U.S.A.
Tel: (1) 305 471 7717 Fax: (1) 305 471 7718

EUROPE

GP BATTERIES EUROPE B.V.
Kortijzer 4, 5721 VE Asten,
The Netherlands
Tel: (31) 493 681030 Fax: (31) 493 681039

GERMANY

GP BATTERY MARKETING (GERMANY) GMBH
Niederlorrycker Str. 62, 40667 Meerbusch, Germany
Tel: (49) 2132 971504/5/6 Fax: (49) 2132 80145

POLAND

GP BATTERY (POLAND) SP. Z.O.O.
ul. Slowicza 19, PL-02170 Warsaw, Poland
Tel: (48) 22 868 0490 Fax: (48) 22 846 7535

U.K.

GP BATTERIES (U.K.) LIMITED
Summerfield Avenue, Chelston Business Park,
Wellington, Somerset, TA21 9JF, U.K.
Tel: (44) 1 823 660 044 Fax: (44) 1 823 665 595

ITALY

GP BATTERY MARKETING ITALY S.R.L.
Via. Alessandro Volta 3,
20094 Assago (Mi), Italy
Tel: (39) 02 488 2512 Fax: (39) 02 488 2865

SCANDINAVIA

GPBM NORDIC AB
Grimboasen 5, SE-417 49, Goteborg, Sweden
Tel: (46) 31 558 600 Fax: (46) 31 556 813

Digital Camera Li-Ion Battery & Charger



Digital Camera Li-Ion Battery & Charger



Many popular digital cameras use AA batteries. To enjoy more shots GP Li-Ion CR-V3 battery, compatible with 2x AA batteries, provides a perfect power solution that lasts longer.

As one of world's top ten battery manufacturers with innovative, advanced battery and charger technology, GP Batteries has specially designed the CR-V3 Li-Ion battery pack to keep digital cameras powered longer whenever shooting.

GP batteries are very reliable, long lasting and fully compatible with OEM brands that use 2x AA batteries like Nikon, Olympus, Samsung, Kodak, Pentax, Konica and Minolta.

Always take the advantage of GP CR-V3 Li-Ion battery pack to power your digital camera.



MAJOR FEATURES For CR-V3 Li-Ion Rechargeable

- Better power solution for major digital cameras using 2 x AA batteries
- Fits for Nikon, Olympus, Samsung, Kodak, Pentax, Konica and Minolta, etc.
- Replacement for CR-V3, like Panasonic, Sanyo, Kodak and Samsung
- Capacity in 1260mAh
- Voltage at 3V



MAJOR FEATURES For Li-Ion Charger

- Charge one CR-V3 Li-Ion rechargeable battery
- Corded type with external adaptor
- AC 100-240V for worldwide use
- Charging time: Approx. 2.5 hours
- Dual colour LED indicator
- Safety timer cutoff
- Safety Protection
 - Over Current Protection
 - Short Circuit Protection
 - Reverse Polarity Protection
- Safety guaranteed

SPECIFICATION

	Li-Ion Charger
Input Voltage	AC100-240V~50/60Hz
Output Voltage	DC9V= 800mA
Charging current	900mA
Battery Type	CR-V3 Li-Ion rechargeable
Dimension	98mm x 29mm x 57mm
	CR-V3 Li-Ion Rechargeable
Voltage	3V
Capacity	1260mAh

